

## TIRES

The ATC250R is equipped with low pressure tubeless tires to promote comfortable riding. Although the tires are designed specifically for vigorous off-road use, they are not immune to punctures. Always select your riding area with care.

### CAUTION:

\* *Driving on paved surfaces will cause excessive tire wear.*

For normal use, the tires should be inflated to a recommended pressure. A manually operated tire pump should be used rather than the high pressure systems found in service stations. This will minimize the possibility of tire damage from overinflation.

### NOTE:

\* Tire pressure should be checked when the tires are "cold," before you ride.

If no air pressure gauge is available to accurately measure a recommended pressure, this value can be estimated by measuring the circumference of the tires with a measuring tape. When inflated to a recommended pressure, the maximum tire circumference measured over the tread ribs will be approximately standard tire circumference. The relationship between tire pressure and actual circumference varies slightly with factors of wear and stretching that occur

through use.

	Recommended pressure	Min. pressure	Max. pressure	Standard tire circumference
Front	3.3 psi (23 kPa, 0.23kg/cm <sup>2</sup> )	2.8 psi (20 kPa, 0.2kg/cm <sup>2</sup> )	3.7 psi (26 kPa, 0.26kg/cm <sup>2</sup> )	1900 mm (74.8 in)
Rear	2.4 psi (17 kPa, 0.17kg/cm <sup>2</sup> )	2.0 psi (14 kPa, 0.14kg/cm <sup>2</sup> )	2.8 psi (20 kPa, 0.2kg/cm <sup>2</sup> )	1745 mm (68.7 in)

### Tire Size

Front : 23.5×8-11

Rear : 22×11.0-8

