

ATC SAFETY

Read these WARNING LABELS before you ride!

REMEMBER

- PRESERVE NATURE
- ALWAYS WEAR A HELMET
- RIDE SAFELY
- READ OWNER'S MANUAL CAREFULLY BEFORE RIDING



▲ WARNING

**OPERATOR ONLY
NO PASSENGERS**

▼ IMPORTANT NOTICE

THIS VEHICLE IS DESIGNED AND MANUFACTURED FOR OFF-THE-ROAD USE ONLY. IT DOES NOT CONFORM TO FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND OPERATION ON PUBLIC STREETS, ROADS, OR HIGHWAYS IS ILLEGAL.

CAUTION

- DO NOT REMOVE RADIATOR CAP WHEN ENGINE IS HOT. ONLY REMOVE CAP WHEN DRAINING COOLANT.
- CHECK THE COOLING SYSTEM FREQUENTLY BY OBSERVING LEVEL IN THE RESERVE TANK. ADD NECESSARY COOLANT AT RESERVE TANK FILLER OPENING.
- USE A 50/50 SOLUTION OF ANTI-FREEZE AND WATER. USE ONLY ANTI-FREEZE OR SUMMER COOLANT RECOMMENDED FOR USE IN ALUMINUM ENGINES.
- USE SOFT WATER (HARD WATER OR SALT WATER IS HARMFUL TO ALUMINUM).
- REFER TO OWNER'S MANUAL FOR COMPLETE INFORMATION.

▼ IMPORTANT INFORMATION MODEL ATC250R

- COLD TIRE PRESSURE
FRONT: 4.3 psi (0.30 kg/cm²)
- TIRE: DUNLOP
FRONT: 23 x 8 - 11
REAR: 20 x 10 - 9
- VEHICLE CAPACITY LOAD: 270 lbs (120 kg)

▼ CAUTION DRIVE CHAIN

- CHECK THE SLACK AND LUBRICATION BEFORE OPERATION
- CHAIN SLACK 1.2 — 1.6 IN.
(30 — 40 mm)