

## SPECIFICATIONS

---

### DIMENSIONS

Overall length . . . . .	1,300 mm (51.2 in)
Overall width . . . . .	800 mm (31.5 in)
Overall height . . . . .	800 mm (31.5 in)
Wheelbase . . . . .	895 mm (35.2 in)

### WEIGHT

Dry weight . . . . .	77 kg (169.8 lbs)
----------------------	-------------------

### CAPACITIES

Engine oil . . . . .	0.8 ℓ (0.8 U.S. qt)
Fuel tank . . . . .	4.3 ℓ (1.1 U.S. gal)
Reserve fuel . . . . .	0.8 ℓ (0.2 U.S. gal)
Passenger capacity . . . .	Operator only

### ENGINE

Bore and stroke . . . . .	47.0 x 41.4 mm (1.850 x 1.630 in)
---------------------------	--------------------------------------

Compression ratio . . . . .	7.5 : 1
Displacement . . . . .	72 cc (4.4 cu. in)
Contact breaker point gap .	0.3 ~ 0.4 mm (0.012 ~ 0.016 in)
Spark plug gap . . . . .	0.6 ~ 0.7 mm (0.024 ~ 0.028 in)
Valve tappet clearance . .	0.05 mm (0.002 in)

### CHASSIS AND SUSPENSION

Caster angle . . . . .	20°
Trail length . . . . .	32 mm (1.26 in)
Tire size, front and rear . .	16 x 8.0 - 7

### POWER TRANSMISSION

Primary reduction . . . . .	4.058
Final reduction . . . . .	2.769
Gear ratio, 1st . . . . .	3.273
2nd . . . . .	1.938
3rd . . . . .	1.350
4th . . . . .	1.043