

Specifications

■ Service Data

Tyre size	Front	110/70-17M/C 54S
	Rear	140/70-17M/C 66S
Tyre type	Bias-ply, tubeless	
Recommended Tyres	Front	IRC RX-01FD
	Rear	IRC RX-01RZ
Tyre air pressure (Driver only)	Front	200 kPa (2.00 kgf/cm ² , 29 psi)
	Rear	200 kPa (2.00 kgf/cm ² , 29 psi)
Tyre air pressure (Driver and passenger)	Front	200 kPa (2.00 kgf/cm ² , 29 psi)
	Rear	225 kPa (2.25 kgf/cm ² , 33 psi)
Minimum tread depth	Front	1.5 mm (0.06 in)
	Rear	2.0 mm (0.08 in)
Spark plugs	(standard) SIMR8A9 (NGK)	
Spark plug gap	(non-adjustable) 0.80 to 0.90 mm (0.031 to 0.035 in)	
Idle speed	1,400 ± 100 rpm	
Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving" or "Resource Conserving" SAE 10W-30, JASO T 903 standard MA	

Engine oil capacity	After draining	1.4 litres (1.5 US qt, 1.2 Imp qt)
	After draining & engine oil filter change	1.5 litres (1.6 US qt, 1.3 Imp qt)
	After disassembly	1.8 litres (1.9 US qt, 1.6 Imp qt)
Recommended brake fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	1.1 litres (1.2 US qt, 1.0 Imp qt)	
Recommended coolant	Pro Honda HP Coolant	