

SPECIFICATIONS

DIMENSIONS

Overall length	2,615 mm (103.0 in)
Overall width	955 mm (37.6 in)
Overall height	1,495 mm (58.9 in)
Wheelbase	1,690 mm (66.5 in)
Ground clearance	115 mm (4.5 in)

WEIGHT

Dry weight (SE)	372 kg (820 lbs) ... (except SI)
(SE)	370 kg (816 lbs) ... (SI)
(ASP)	370 kg (816 lbs)

CAPACITIES

Engine oil	
—After draining	3.5 ℓ (3.1 Imp qt, 3.7 US qt)
—After oil filter change	3.7 ℓ (3.3 Imp qt, 3.9 US qt)
—After disassembly	4.3 ℓ (3.8 Imp qt, 4.5 US qt)
Final drive gear oil	
—After draining	140 cm ³ (4.9 Imp oz, 4.7 US oz)
Fuel tank	23 ℓ (5.1 Imp gal, 6.1 US gal)
Cooling system capacity	4.1 ℓ (3.6 Imp qt, 4.3 US qt)
Passenger capacity	Operator and one passenger
Maximum weight (SE)	180 kg (397 lbs) (E, F, ED, FI, AR, SP)
capacity (SE)	175 kg (386 lbs) ... (SW)
(SE)	185 kg (408 lbs) ... (SI)
(ASP)	182 kg (401 lbs)

ENGINE

Bore and stroke	71 x 64 mm (2.8 x 2.5 in)
Compression ratio	9.8 : 1
Displacement	1,520 cc (92.7 cu.in)
Spark plug	
Standard	X22EPR-U9 (NIPPONDENSO), DPR7EA-9 (NGK)
For E type:	X20EPR-U9 (NIPPONDENSO), DPR6EA-9 (NGK)
For cold climate (Below 5°C, 41°F)	X20EPR-U9 (NIPPONDENSO), DPR6EA-9 (NGK)
For extended high speed riding	X24EPR-U9 (NIPPONDENSO), DPR8EA-9 (NGK)
For E type:	X22EPR-U9 (NIPPONDENSO), DPR7EA-9 (NGK)