

SPECIFICATIONS

DIMENSIONS

Overall length	2,635 mm (103.7 in)
Overall width	945 mm (37.2 in)
Overall height	1,455 mm (57.3 in)
Wheelbase	1,690 mm (66.5 in)
Ground clearance	125 mm (4.9 in)

WEIGHT

Dry weight	363 kg (800 lbs)
------------	------------------

CAPACITIES

Engine oil	
– After disassembly	4.6 ℓ (4.9 US qt , 4.0 Imp qt)
– After oil filter change	3.7 ℓ (3.9 US qt , 3.3 Imp qt)
– After draining	3.6 ℓ (3.8 US qt , 3.2 Imp qt)
Final drive gear oil	
– After draining	120 cm ³ (4.1 US oz , 4.2 Imp oz)
Fuel tank	25 ℓ (6.6 US gal , 5.5 Imp gal)
Cooling system capacity	3.5 ℓ (3.7 US qt , 3.1 Imp qt)
Passenger capacity	Operator and one passenger
Maximum weight capacity	200 kg (441 lbs)

ENGINE

Bore and stroke	74.0 × 71.0 mm (2.90 × 2.80 in)
Compression ratio	9.8 : 1
Displacement	1,832 cm ³ (111.8 cu-in)
Spark plug	
standard	BKR6E-11 (NGK) or K20PR-U11 (DENSO)
For cold climate (Below 5° C, 41° F)	BKR5E-11 (NGK) or K16PR-U11 (DENSO)
For extended high speed riding	BKR7E-11 (NGK) or K22PR-U11 (DENSO)
Spark plug gap	1.00 – 1.10 mm (0.039 – 0.043 in)
Idle speed	700 ± 70 min ⁻¹ (rpm)
Valve clearance (cold)	Intake: 0.15 mm (0.006 in) Exhaust: 0.22 mm (0.009 in)