



SPECIFICATIONS

DIMENSIONS

| | |
|----------------|---------------------|
| Overall length | 2,605 mm (102.6 in) |
| Overall width | 945 mm (37.2 in) |
| Overall height | 1,255 mm (49.4 in) |
| Wheelbase | 1,690 mm (66.5 in) |

CAPACITIES

| | |
|---------------------------|--|
| Engine oil | |
| — After disassembly | 4.6 ℓ (4.9 US qt , 4.0 Imp qt) |
| — After oil filter change | 3.7 ℓ (3.9 US qt , 3.3 Imp qt) |
| — After draining | 3.6 ℓ (3.8 US qt , 3.2 Imp qt) |
| Final drive gear oil | |
| — After draining | 120 cm ³ (4.1 US oz , 4.2 Imp oz) |
| Fuel tank | 25 ℓ (6.6 US gal , 5.5 Imp gal) |
| Cooling system capacity | 4.5 ℓ (4.8 US qt , 4.0 Imp qt) |
| Passenger capacity | Operator and one passenger |
| Maximum weight capacity | 190 kg (419 lb) ...Except KO type 172 kg (379 lb) ...KO type only |

ENGINE

| | |
|---|---|
| Bore and stroke | 74.0 × 71.0 mm (2.91 × 2.80 in) |
| Compression ratio | 9.8 ± 0.2 : 1 |
| Displacement | 1,832 cm ³ (111.8 cu-in) |
| Spark plug standard | BKR6E-11 (NGK) or K20PR-U11 (DENSO) |
| For cold climate (Below 5° C, 41° F) | BKR5E-11 (NGK) or K16PR-U11 (DENSO) |
| For extended high speed riding | BKR7E-11 (NGK) or K22PR-U11 (DENSO) |
| Spark plug gap | 1.00 – 1.10 mm (0.039 – 0.043 in) |
| Idle speed | 730 ± 70 min ⁻¹ (rpm) |
| Valve clearance (cold) | Intake: 0.15 mm (0.006 in) Exhaust: 0.22 mm (0.009 in) |

