

# Specifications

<b>Lights (cont'd)</b>	
PGM-FI malfunction indicator lamp (MIL)	12 V 3.4 W
parking brake indicator	12 V 3.4 W
4WD indicator	12 V 3.4 W
front differential lock indicator	12 V 3.4 W

<b>Fuses</b>	
main	30 A
circuit	15 A×2 , 10 A×4

<b>Torque Specification</b>	
seat-back mount bolts	9 lbf·ft (12 N·m , 1.2 kgf·m)
engine oil drain bolt	18 lbf·ft (25 N·m , 2.5 kgf·m)
engine oil filter bolt	13 lbf·ft (18 N·m , 1.8 kgf·m)
maintenance lid mount bolts	9 lbf·ft (12 N·m , 1.2 kgf·m)
right seat mount pipe mount bolt A	16 lbf·ft (22 N·m , 2.2 kgf·m)
right seat mount pipe mount bolts B	20 lbf·ft (27 N·m , 2.8 kgf·m)
front differential oil drain bolt	9 lbf·ft (12 N·m , 1.2 kgf·m)
front differential oil filler cap	9 lbf·ft (12 N·m , 1.2 kgf·m)
rear differential oil drain bolt	9 lbf·ft (12 N·m , 1.2 kgf·m)
rear differential oil filler cap	9 lbf·ft (12 N·m , 1.2 kgf·m)
spark arrester mount bolts	9 lbf·ft (12 N·m , 1.2 kgf·m)
wheel nuts	79.7 lbf·ft (108 N·m , 11.0 kgf·m)