

MAINTENANCE SCHEDULE

Perform the Pre-ride Inspection at each scheduled maintenance period.

I : INSPECT AND CLEAN, ADJUST, LUBRICATE OR REPLACE IF NECESSARY

C : CLEAN R : REPLACE A : ADJUST L : LUBRICATE

ITEM	FREQUENCY	WHICHEVER COMES FIRST ↓ →	ODOMETER READING [NOTE (2)]							PAGE
			1,000 km (600 mi)	6,000 km (3,750 mi)	12,000 km (7,500 mi)	18,000 km (11,250 mi)	24,000 km (15,000 mi)	30,000 km (18,750 mi)	36,000 km (22,500 mi)	
	EVERY									
* FUEL LINES					I		I		I	
* FUEL STRAINER SCREEN				C	C	C	C	C	C	
* THROTTLE OPERATION					I		I		I	138
** OIL PUMP AND OIL LINE			I		I		I		I	
* CARBURETOR-CHOKE					I		I		I	
* AIR CLEANER	NOTE (1)			C	C	C	C	C	C	134
SPARK PLUGS			EVERY 3,000 km (1,875 mi)					I		130
			EVERY 6,000 km (3,750 mi)					R		
** DECARBONIZING					C		C		C	
* CARBURETOR- SYNCHRONIZATION			I		I		I		I	
* CARBURETOR-IDLE SPEED			I	I	I	I	I	I	I	140
RADIATOR COOLANT	2 YEARS*R				I		I		*R	188
* COOLING SYSTEM					I		I		I	