

MAINTENANCE SCHEDULE

Perform the Pre-ride Inspection at each scheduled maintenance period.

I : INSPECT AND CLEAN, ADJUST, LUBRICATE OR REPLACE IF NECESSARY

C : CLEAN R : REPLACE A : ADJUST L : LUBRICATE

ITEM	FREQUENCY	WHICHEVER COMES FIRST ↓ →	ODOMETER READING [NOTE (3)]							PAGE
			1,000 km (600 mi)	6,000 km (3,750 mi)	12,000 km (7,500 mi)	18,000 km (11,250 mi)	24,000 km (15,000 mi)	30,000 km (18,750 mi)	36,000 km (22,500 mi)	
	EVERY									
* FUEL LINES					I		I		I	
* FUEL STRAINER			C	C	C	C	C	C	C	
* THROTTLE OPERATION				I		I		I		122
* CARBURETOR-CHOKE				I		I		I		
* AIR CLEANER	NOTE (1)			R		R		R		118
CRANKCASE BREATHER	NOTE (2)		C	C	C	C	C	C	C	128
SPARK PLUGS			I	R	I	R	I	R		114
* VALVE CLEARANCE		I	I	I		I		I		
ENGINE OIL	YEAR	R		R		R		R		108
ENGINE OIL FILTER	YEAR	R		R		R		R		110
* CARBURETOR- SYNCHRONIZATION		I		I		I		I		
* CARBURETOR- IDLE SPEED		I	I	I	I	I	I	I	I	124
RADIATOR COOLANT				I		I		*R		168
* RADIATOR CORE				I		I		I		
* COOLING SYSTEM HOSES & CONNECTIONS				I		I		I		
DRIVE CHAIN			I, L EVERY 1,000 km (600 mi)							130