


MAINTENANCE SCHEDULE

Perform the Pre-ride Inspection at each scheduled maintenance period.

I: Inspect and Clean, Adjust, Lubricate or Replace if necessary.

C: Clean R: Replace A: Adjust L: Lubricate

ITEM	FREQUENCY	WHICHEVER COMES FIRST 	ODOMETER READING [NOTE (3)]							PAGE
			1,000 km (600 mi)	6,000 km (3,750 mi)	12,000 km (7,500 mi)	18,000 km (11,250 mi)	24,000 km (15,000 mi)	30,000 km (18,750 mi)	36,000 km (22,500 mi)	
	EVERY									
* FUEL LINE				I		I		I		
* FUEL STRAINER SCREEN			C	C	C	C	C	C		
* THROTTLE OPERATION				I		I		I		
* CARBURETOR CHOKE				I		I		I		
AIR CLEANER	(NOTE 1)				R			R	35	
CRANKCASE BREATHER	(NOTE 2)		C	C	C	C	C	C	38	
SPARK PLUG			I	R	I	R	I	R	34	
* VALVE CLEARANCE			I		I		I			
ENGINE OIL			R		R		R		31	
ENGINE OIL FILTER			R		R		R		32	
* CARBURETOR SYNCHRONIZATION			I	I	I	I	I	I		
* CARBURETOR IDLE SPEED			I	I	I	I	I	I	37	
RADIATOR COOLANT	2 YEARS *R			I		I		*R		
* COOLING SYSTEM				I		I		I		