

Safety Labels

< For USA >

TIRE INFORMATION		
Cold tire pressures: [Up to maximum weight capacity]	Tire brand	Front Rear
	DUNLOP D404F D404	
Front 200kPa 2.00kgf/cm ² 29psi	BRIDGESTONE EXEDRA G701	Rear D404 EXEDRA G702
Rear 250kPa 2.50kgf/cm ² 36psi	Min. recommend tire center tread depth.	
[Up to 90kg(200lbs) load]	Front 1.5mm(0.06in.)	Rear 2.0mm(0.08in.)
Front 200kPa 2.00kgf/cm ² 29psi	Read owner's manual.	
Rear 200kPa 2.00kgf/cm ² 29psi		
Maximum weight capacity:180kg(397lbs)		
Tire size: Front 90/90-21M/C 54S		
Rear 160/80-15M/C 74S		

< For Canada >

TIRE INFORMATION		
Cold tire pressures: [Up to maximum weight capacity]	Tire brand	Front Rear
	DUNLOP D404F D404	
Front 200kPa 2.00kgf/cm ² 29psi	BRIDGESTONE EXEDRA G701	Rear D404 EXEDRA G702
Rear 250kPa 2.50kgf/cm ² 36psi	Min. recommend tire center tread depth.	
[Up to 90kg(200lbs) load]	Front 1.5mm(0.06in.)	Rear 2.0mm(0.08in.)
Front 200kPa 2.00kgf/cm ² 29psi	Read owner's manual.	
Rear 200kPa 2.00kgf/cm ² 29psi		
Maximum weight capacity:184kg(406lbs)		
Tire size: Front 90/90-21M/C 54S		
Rear 160/80-15M/C 74S		

