

MAINTENANCE SCHEDULE

Perform Pre-ride Inspection (Page 66) at each scheduled maintenance period.

I: Inspect and Clean, Adjust, Lubricate or Replace if necessary.

C: Clean R: Replace A: Adjust L: Lubricate

ITEM	FREQUENCY	WHICHEVER COMES FIRST ↓	ODOMETER READING [NOTE(1)]				REFER TO PAGE	
			x1000km	1	4	8		12
			x1000mi	0.6	2.5	5		7.5
	EVERY	MONTHS		6	12	18		
* FUEL LINE				I	I	I		
* FUEL STRAINER SCREEN				C	C	C		
* THROTTLE OPERATION				I	I	I	116	
* CARBURETOR-CHOKE				I	I	I		
AIR CLEANER	NOTE (2)			C	C	C	114	
SPARK PLUG				I	R	I	104	
* VALVE CLEARANCE			I	I	I	I	106	
ENGINE OIL			R	EVERY 2,000km (1,250 mi) R			94	
ENGINE OIL STRAINER SCREEN						C	96	
** ENGINE OIL CENTRIFUGAL FILTER						C	100	
* DECOMPRESSOR SYSTEM			I	I	I	I	110	
* CAN CHAIN TENSION			A	A	A	A	112	
* CARBURETOR-IDLE SPEED			I	I	I	I	118	