

■ Service Data

Tire size	Front	120/70ZR17M/C (58W)
	Rear	190/55ZR17M/C (75W)
Tire type	Radial, tubeless	
Recommended Tire	Front	BRIDGESTONE BATTLEAX HYPERSPORT S21F M
		DUNLOP SPORTMAX D214F G
	Rear	BRIDGESTONE BATTLEAX HYPERSPORT S21R M
		DUNLOP SPORTMAX D214 G
Tire air pressure	Front	36 psi (250 kPa, 2.50 kgf/cm <sup>2</sup> )
	Rear	42 psi (290 kPa, 2.90 kgf/cm <sup>2</sup> )
Minimum tread depth	Front	0.06 in (1.5 mm)
	Rear	0.08 in (2.0 mm)
Spark plug	(standard)	IMR9E-9HES (NGK) or VUH27ES (DENSO)
Spark plug gap	0.03 - 0.04 in (0.8 - 0.9 mm)	
Idle speed	1,200 ± 100 rpm	

Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	
	After draining	2.9 US qt (2.7 L)
Engine oil capacity	After draining & engine oil filter change	3.2 US qt (3.0 L)
	After disassembly	3.8 US qt (3.6 L)
Recommended brake fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	2.91 US qt (2.75 L)	
Recommended coolant	Pro Honda HP Coolant	
Recommended drive chain lubricant	Pro Honda HP Chain Lube or equivalent lubricant	
Drive chain slack	1 9/16 - 1 15/16 in (40 - 50 mm)	
Standard drive chain	RK525ROZ7	
	No. of links	116
Standard sprocket size	Drive sprocket	15T
	Driven sprocket	44T