

Specifications

■ Bulbs

| | |
|--------------------------|---------------|
| Headlight | 12V-60/55W |
| Brake light | LED |
| Taillight | LED |
| Front turn signal lights | 12V-21/5W x 2 |
| Rear turn signal lights | 12V-21W x 2 |
| Position light | LED |
| License plate light | 12V-5W |

■ Fuses

| | |
|-------------|----------|
| Main fuse | 30A |
| FI fuse | 20A |
| Other fuses | 20A, 10A |

■ Torque Specifications

| | |
|--|---------------------------------|
| Engine oil drain bolt | 22 lbf-ft (30 N·m, 3.1 kgf·m) |
| Oil filter | 19 lbf-ft (26 N·m, 2.7 kgf·m) |
| Bearing holder pinch bolt | 65 lbf-ft (88 N·m, 9.0 kgf·m) |
| Front wheel axle bolt | 44 lbf-ft (59 N·m, 6.0 kgf·m) |
| Front wheel brake caliper mounting bolts | 33 lbf-ft (45 N·m, 4.6 kgf·m) |
| Front wheel axle pinch bolts | 16 lbf-ft (22 N·m, 2.2 kgf·m) |
| Rear wheel nuts | 80 lbf-ft (108 N·m, 11.0 kgf·m) |
| Muffler mount bolt A | 16 lbf-ft (22 N·m, 2.2 kgf·m) |
| Muffler mount bolt B and nut | 16 lbf-ft (22 N·m, 2.2 kgf·m) |
| Muffler band bolt | 16 lbf-ft (22 N·m, 2.2 kgf·m) |