





| Items                      |   | Frequency*1   |          |          |          |          |          |          |          | Refer to page |
|----------------------------|---|---|----------|----------|----------|----------|----------|----------|----------|---------------|
|                            |   | × 1,000 mi  | 0.6      | 4        | 8        | 12       | 16       | 20       | 24       |               |
|                            |   | × 1,000 km  | 1.0      | 6.4      | 12.8     | 19.2     | 25.6     | 32.0     | 38.4     |               |
| Non-Emission-Related Items | Drive Chain   | Every 500 mi (800 km): <b>I L</b>   |          |          |          |          |          |          |          | 79            |
|                            | Brake Fluid*4   |   |          | <b>I</b> | <b>I</b> | <b>R</b> | <b>I</b> | <b>I</b> | <b>R</b> | 76            |
|                            | Brake Pads Wear   |   |          | <b>I</b> | <b>I</b> | <b>I</b> | <b>I</b> | <b>I</b> | <b>I</b> | 77            |
|                            | Brake System  |   | <b>I</b> |          | <b>I</b> |          | <b>I</b> |          | <b>I</b> | 76            |
|                            | Brake Light Switch  |   |          |          | <b>I</b> |          | <b>I</b> |          | <b>I</b> | 92            |
|                            | Headlight Aim   |   |          |          | <b>I</b> |          | <b>I</b> |          | <b>I</b> | 92            |
|                            | Clutch System   |   | <b>I</b> | <b>I</b> | <b>I</b> | <b>I</b> | <b>I</b> | <b>I</b> | <b>I</b> | 83            |
|                            | Side Stand  |   |          |          | <b>I</b> |          | <b>I</b> |          | <b>I</b> | 78            |
|                            | Suspension  |  |          |          | <b>I</b> |          | <b>I</b> |          | <b>I</b> | 88            |
|                            | Nuts, Bolts, Fasteners  |  |          | <b>I</b> |          | <b>I</b> |          | <b>I</b> | <b>I</b> | -             |
|                            | Wheels/Tires  |  |          |          | <b>I</b> |          | <b>I</b> |          | <b>I</b> | 61            |
| Steering Head Bearings     |  |   | <b>I</b> |          | <b>I</b> |          | <b>I</b> | <b>I</b> | -        |               |

**Notes:**

- \*1 : At higher odometer readings, repeat at the frequency interval established here.
- \*2 : Service more frequently when riding in unusually wet or dusty areas.
- \*3 : 50 STATE type (meets California).
- \*4 : Replace every 2 years, or at indicated odometer intervals, whichever comes first. Replacement requires mechanical skill.