

■ **Service Data**

| | | |
|----------------------------|---|---|
| Tire size | Front | 120/70ZR17M/C (58W) |
| | Rear | 180/55ZR17M/C (73W) |
| Tire type | Radial, tubeless | |
| Recommended Tire | Front | DUNLOP D214F K |
| | Rear | DUNLOP D214 K |
| Tire air pressure | Front | 36 psi (250 kPa, 2.50 kgf/cm ²) |
| | Rear | 42 psi (290 kPa, 2.90 kgf/cm ²) |
| Minimum tread depth | Front | 0.06 in (1.5 mm) |
| | Rear | 0.08 in (2.0 mm) |
| Spark plug | (standard) | VUH27D (DENSO) |
| Spark plug gap | (non-adjustable) | 0.03 - 0.04 in (0.8 - 0.9 mm) |
| Idle speed (no adjustment) | 1,400 ± 100 rpm | |
| Recommended engine oil | API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil | |

| | | |
|-----------------------------------|---|-------------------|
| Engine oil capacity | After draining | 2.9 US qt (2.7 L) |
| | After draining & engine oil filter change | 3.0 US qt (2.8 L) |
| Recommended brake fluid | After disassembly | 3.7 US qt (3.5 L) |
| | Honda DOT 4 Brake Fluid | |
| Cooling system capacity | 3.2 US qt (3.0 L) | |
| Recommended coolant | Pro Honda HP Coolant | |
| Recommended drive chain lubricant | Pro Honda HP Chain Lube or equivalent | |
| Drive chain slack | 1 3/16 - 1 9/16 in (30 - 40 mm) | |
| Standard drive chain | DID525HV or RK525ROZ6 | |
| | No. of links | 112 |
| Standard sprocket size | Drive sprocket | 16T |
| | Driven sprocket | 42T |