

Specifications

■ Main Components

Overall length	86.8 in (2,205 mm)
Overall width	32.3 in (820 mm)
Overall height	42.9 in (1,090 mm)
Wheelbase	58.7 in (1,490 mm)
Minimum ground clearance	5.9 in (150 mm)
Caster angle	28°
Trail	4.3 in (110 mm)

Curb weight	CMX300	
	49 STATE	364 lb (165 kg)
	50 STATE (meets California)	366 lb (166 kg)

Curb weight	CMX300A	
	50 STATE (meets California)	370 lb (168 kg)
	Canada model	368 lb (167 kg)

Maximum weight capacity	Model not equipped with Optional Passenger Seat Kit *1	346 lb (157 kg)
	Model equipped with Optional Passenger Seat Kit *2	346 lb (157 kg)

*1 : Including rider, all luggage, and accessories

*2 : Including rider, passenger, all luggage, and accessories

Passenger capacity	Model not equipped with Optional Passenger Seat Kit	Rider only (no passenger)
	Model equipped with Optional Passenger Seat Kit	Rider and 1 passenger
Minimum turning radius	9.2 ft (2.8 m)	
Displacement	17.4 cu-in (286 cm ³)	
Bore x stroke	2.99 x 2.48 in (76.0 x 63.0 mm)	
Compression ratio	10.7 : 1	
Fuel	Unleaded gasoline Recommended: 86 PON or higher	
Tank capacity	2.96 US gal (11.2 L)	
Battery	YTZ8V	
	12 V-7 Ah (10 HR)	
Gear ratio	1st	3.416
	2nd	2.250
	3rd	1.650
	4th	1.350
	5th	1.166
	6th	1.038
Reduction ratio (primary / final)	2.807 / 2.571	