

# Specifications

| <b>Chassis &amp; Suspension</b> |   |
|---------------------------------|---|
| Caster                          | 27° 30'   |
| Trail                           | CRF125F:<br>3.2 in (81 mm)<br>CRF125FB:<br>3.7 in (94 mm)     |
| Tire size,<br>front             | CRF125F:<br>70/100-17M/C 40M<br>CRF125FB:<br>70/100-19M/C 42M |
| Tire size,<br>rear              | CRF125F:<br>90/100-14M/C 49M<br>CRF125FB:<br>90/100-16M/C 51M |

| <b>Chassis &amp; Suspension</b> |   |
|---------------------------------|---|
| Tire type                       | bias-ply, tube  |
| Tire pressure,<br>front (cold)  | 15 psi (100 kPa, 1.0 kgf/cm <sup>2</sup> )  |
| Tire pressure,<br>rear (cold)   | 15 psi (100 kPa, 1.0 kgf/cm <sup>2</sup> )  |
| Suspension,<br>front            | CRF125F:<br>4.9 in (124 mm)<br>axle travel<br>CRF125FB:<br>5.2 in (133 mm)<br>axle travel |
| Suspension,<br>rear             | CRF125F:<br>4.5 in (114 mm)<br>axle travel<br>CRF125FB:<br>5.9 in (150 mm)<br>axle travel |