

Specifications

| | | |
|----------------------------------|--------------------------|----------------------------------|
| Recommended final drive oil | Hypoid gear oil SAE 80 | |
| Final drive oil capacity | After draining | 4.7 US oz (140 cm ³) |
| | After disassembly | 5.4 US oz (160 cm ³) |
| Recommended brake (clutch) fluid | Honda DOT 4 Brake Fluid | |
| Cooling system capacity | 3.06 US qt (2.90 liters) | |
| Recommended coolant | Pro Honda HP Coolant | |

■ Bulbs

| | |
|-------------------------|-----|
| Headlight | LED |
| Brake light | LED |
| Taillight | LED |
| Front turn signal light | LED |
| Rear turn signal light | LED |
| License plate light | LED |

■ Fuses

| | |
|--|-----------------------|
| Ignition main fuse | 30 A |
| ACC main fuse | 20 A |
| Main fuse B | 120 A |
| Speed limiter fuse (Except GL1800B USA model) | 60 A |
| External amplifier fuse | 40 A |
| Other fuse | 30 A, 15 A, 10 A, 5 A |

■ Torque Specifications

| | |
|---|---------------------------------|
| Oil filter | 19 lbf-ft (26 N·m, 2.7 kgf·m) |
| Engine oil drain bolt | 22 lbf-ft (30 N·m, 3.1 kgf·m) |
| Final drive oil fill hole cap | 5.9 lbf-ft (8 N·m, 0.8 kgf·m) |
| Final drive oil drain bolt | 9 lbf-ft (12 N·m, 1.2 kgf·m) |
| Front wheel axle bolt | 44 lbf-ft (59 N·m, 6.0 kgf·m) |
| Front wheel axle pinch bolt | 16 lbf-ft (22 N·m, 2.2 kgf·m) |
| Front wheel brake caliper mounting bolt | 31 lbf-ft (42.5 N·m, 4.3 kgf·m) |
| Rear wheel nut | 80 lbf-ft (108 N·m, 11 kgf·m) |