

Safety Labels

Safety and information labels on your motorcycle provide important safety information and may warn you of potential

hazards that could cause serious injury. Read these labels carefully and don't remove them. If a label comes off or becomes hard to read, contact your dealer for a replacement.

TIRE INFORMATION		
Cold tire pressures :	Tire brand	Front Rear
Up to maximum weight capacity	DUNLOP	D423F K D423 K
Front 225kPa 2,25kg/cm ² 33psi	Min. recommend tire center tread depth.	
Rear 250kPa 2,50kg/cm ² 36psi	Front 1,5mm(0,06in.) Rear 2,0mm(0,08in.)	
Up to 90kg(200lbs) load	Read owner's manual.	
Front 225kPa 2,25kg/cm ² 33psi	This motorcycle is equipped with tubeless tires.	
Rear 250kPa 2,50kg/cm ² 36psi		
Maximum weight capacity :157kg(346lbs)		
Tire size : Front 120/70ZR18M/C(59W)		
Rear 200/50ZR17M/C(75W)		

Cargo Limit
3.0kg / 6.6lbs

CARGO LIMIT
2.0kg / 4.5lbs

DANGER WARNING
危険 険
▶ NEVER OPEN WHEN HOT.
Hot coolant will scald you.
▶ N'OUVREZ PAS QUAND CHAUD.
▶ NIGHT BEI HEISSEN MOTOR OFFEN.
▶ 熱い時 開けないで下さい。
▶ 高温時、請勿打开。

1.1