

Recommended coolant	Pro Honda HP Coolant
Recommended drive chain lubricant	Pro Honda HP Chain Lube or equivalent
Drive chain slack	13/16 to 1 3/16 in (20 to 30 mm)
Standard drive chain	DID520V0 or RK520KHO No. of links 112
Standard sprocket sizes	Front sprocket NC700JD 16T NC750JD 17T Rear wheel sprocket 39T

■ Lights

Headlight	LED
Brake/Tail light	LED
Front turn signal/Position lights	LED
Rear turn signal lights	LED
License plate light	LED

■ Fuses

Main fuse	30A
Other fuses	30A, 15A, 7.5A

■ Torque Specifications

Engine oil drain bolt	22 lbf·ft (30 N·m, 3.1 kgf·m)
Oil filter	19 lbf·ft (26 N·m, 2.7 kgf·m)
Front wheel axle bolt	44 lbf·ft (59 N·m, 6.0 kgf·m)
Front wheel brake caliper mounting bolts	22 lbf·ft (30 N·m, 3.1 kgf·m)
Front wheel axle pinch bolt	16 lbf·ft (22 N·m, 2.2 kgf·m)
Rear wheel axle nut	72 lbf·ft (98 N·m, 10.0 kgf·m)
Drive chain adjusting lock nuts	15 lbf·ft (21 N·m, 2.1 kgf·m)
Parking brake caliper mounting bolts	23 lbf·ft (31 N·m, 3.2 kgf·m)