

	NC700X/750XA		
	1st	2.812	
	2nd	1.894	
	3rd	1.454	
	4th	1.200	
	5th	1.033	
	6th	0.837	
Gear ratios	NC700XD/750XD		
	1st	2.666	
	2nd	1.904	
	3rd	1.454	
	4th	1.200	
	5th	1.033	
	6th	NC700XD	0.837
		NC750XD	0.864
	Reduction ratios (primary / final)	NC700X	1.731 / 2.687
		NC700XD	1.921 / 2.437
NC750XA		1.731 / 2.529	
NC750XD		1.921 / 2.294	

■ Service Data

Tire size	Front	120/70ZR17M/C (58W)
	Rear	160/60ZR17M/C (69W)
Tire type	Radial, tubeless	
Recommended Tires	Front	DUNLOP D609F BRIDGESTONE BW-501 RADIAL G
	Rear	DUNLOP D609 BRIDGESTONE BW-502 RADIAL G
Tire air pressure	Front	36 psi (250 kPa, 2.50 kgf/cm ²)
	Rear	42 psi (290 kPa, 2.90 kgf/cm ²)
Minimum tread depth	Front	0.06 in (1.5 mm)
	Rear	0.08 in (2.0 mm)
Spark plugs	(standard)	IFR6G-11K (NGK)
Spark plug gap	(non-adjustable)	0.039 to 0.043 in (1.00 to 1.10 mm)
Idle speed	1,200 ± 100 rpm	
Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	