

## ■ Service Data

Tire size	Front	80/100-10 46J
	Rear	80/100-10 46J
Tire type		Bias-ply, tubeless
Recommended Tire	Front	CHENG SHIN C-6161
	Rear	CHENG SHIN C-6161
Tire air pressure	Front	18 psi (125 kPa, 1.25 kgf/cm <sup>2</sup> )
	Rear	29 psi (200 kPa, 2.00 kgf/cm <sup>2</sup> )
Spark plug	(standard)	CPR8EA-9 (NGK)
Spark plug gap		0.031 - 0.035 in (0.80 - 0.90 mm)
Idle speed		2,000 ± 100 rpm

API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MB, Pro Honda HP4M 4-stroke oil or an equivalent motorcycle oil

Engine oil capacity	After draining	0.68 US qt (0.64 L)
	After draining & engine oil strainer screen cleaning	0.69 US qt (0.65 L)
	After disassembly	0.74 US qt (0.7 L)
Cooling system capacity		0.33 US qt (0.31 L)
Recommended coolant		Pro Honda HP Coolant

## ■ Bulbs

Headlight	12 V-35/35 W
Brake light/Taillight	12 V-21/5 W
Front turn signal light	12 V-10 W × 2
Rear turn signal light	12 V-10 W × 2

## ■ Fuses

Main fuse	25 A
Other fuse	10 A

## ■ Torque Specifications

Engine oil drain bolt	18 lbf-ft (24 N-m, 2.4 kgf-m)
Engine oil plug	15 lbf-ft (20 N-m, 2.0 kgf-m)