

Specifications

| Fuses | |
|----------------------------|--------------------------------|
| main | 50 A |
| circuit | 30 A, 20 A, 15 A x 4, 10 A x 3 |
| EPS (except for SXS1000M3) | 40 A |

| Torque Specification | |
|---------------------------------|-------------------------------|
| engine oil filter cover bolts | 9 lbf·ft (12 N·m, 1.2 kgf·m) |
| DCT oil filter cover bolts | 9 lbf·ft (12 N·m, 1.2 kgf·m) |
| engine oil drain bolts | 22 lbf·ft (30 N·m, 3.1 kgf·m) |
| sub-transmission oil drain bolt | 22 lbf·ft (29 N·m, 3.0 kgf·m) |
| front final gear oil fill cap | 9 lbf·ft (12 N·m, 1.2 kgf·m) |
| front final gear oil drain plug | 9 lbf·ft (12 N·m, 1.2 kgf·m) |
| rear final gear oil fill cap | 9 lbf·ft (12 N·m, 1.2 kgf·m) |
| rear final gear oil drain plug | 9 lbf·ft (12 N·m, 1.2 kgf·m) |
| spark arrester mount bolts | 9 lbf·ft (12 N·m, 1.2 kgf·m) |
| wheel nuts | 80 lbf·ft (108 N·m, 11 kgf·m) |