## **Specifications**

| Capacities              |   |
|-------------------------|---|
| passenger<br>capacity   | operator only                                       |
| maximum weight capacity | 243 lb (110 kg)<br>rider, all cargo and accessories |

| Engine Specifications |                                 |  |  |
|-----------------------|---------------------------------|--|--|
| displacement          | 27.4 cu-in (449 cm³)            |  |  |
| bore & stroke         | 3.78 × 2.44 in (96.0 × 62.1 mm) |  |  |
| compression ratio     | 12.0 : 1                        |  |  |
| spark plug            | IFR7L11 (NGK)                   |  |  |
| (standard)            | or VK22PRZ11 (DENSO)            |  |  |
| spark plug (high      | IFR8H11 (NGK)                   |  |  |
| speed riding)         | or VK24PRZ11 (DENSO)            |  |  |
| spark plug gap        | 0.039 – 0.043 in (1.0 – 1.1 mm) |  |  |
| valve clearance       | intake: 0.006 in (0.16 mm)      |  |  |
| (cold)                | exhaust: 0.011 in (0.28 mm)     |  |  |
| idle speed            | 1,700 ± 100 rpm                 |  |  |

| Power Transmission |     |               |  |  |
|--------------------|-----|---------------|--|--|
| primary reduction  |     | 2.739         |  |  |
| final reduction    |     | 2.923         |  |  |
| gear ratio         | 1st | 2.230         |  |  |
|                    | 2nd | 1.785         |  |  |
|                    | 3rd | 1.437         |  |  |
|                    | 4th | 1.181         |  |  |
|                    | 5th | 0.962         |  |  |
| final drive        |     | chain         |  |  |
|                    |     | DID520V or    |  |  |
|                    |     | RK520 SMOZ10S |  |  |