

VT1300CXA IICM type

TIRE INFORMATION

COLD TIRE PRESSURES :
 [UP TO MAXIMUM WEIGHT CAPACITY] FRONT 225 kPa 2.25kgf/cm² 33psi.
 REAR 280kPa 2.80kgf/cm² 41psi.
 [UP TO 90kg (200lbs.) LOAD] FRONT 225 kPa 2.25kgf/cm² 33psi.
 REAR 280kPa 2.80kgf/cm² 41psi.
MAXIMUM WEIGHT CAPACITY : 146 kg (322 lbs.)
TIRE SIZE : FRONT 90/90-21M/C 54H REAR 200/50R18M/C 76H

| TIRE BRAND | FRONT | REAR |
|------------|--------|--------|
| DUNLOP | D422F | D423 |
| METZELER | ME 880 | ME 880 |

Read Owner's Manual

MIN. RECOMMEND TIRE CENTER TREAD DEPTH
 FRONT 1.5mm (0.06in.) REAR 2.0mm (0.08in.)

THIS MOTORCYCLE IS EQUIPPED WITH TUBELESS TIRES.

Except VT1300CXA IICM type

TIRE INFORMATION

COLD TIRE PRESSURES : FRONT 225 kPa 2.25kgf/cm² 33psi.
 REAR 280kPa 2.80kgf/cm² 41psi.
MAXIMUM WEIGHT CAPACITY : 110 kg (243 lbs.)
TIRE SIZE : FRONT 90/90-21M/C 54H REAR 200/50R18M/C 76H

| TIRE BRAND | FRONT | REAR |
|------------|--------|--------|
| DUNLOP | D422F | D423 |
| METZELER | ME 880 | ME 880 |

Read Owner's Manual

MIN. RECOMMEND TIRE CENTER TREAD DEPTH
 FRONT 1.5mm (0.06in.) REAR 2.0mm (0.08in.)

THIS MOTORCYCLE IS EQUIPPED WITH TUBELESS TIRES.

