

Specifications

■ Service Data

Tire size	Front	90/90-21M/C 54H
	Rear	200/50R18M/C 76H
Tire type	Front	Bias-ply, tubeless
	Rear	Radial, tubeless
Recommended Tire	Front	DUNLOP D422F METZELER ME 880
	Rear	DUNLOP D423 METZELER ME 880
Tire air pressure	Front	33 psi (225 kPa, 2.25 kgf/cm ²)
	Rear	41 psi (280 kPa, 2.80 kgf/cm ²)
Minimum tread depth	Front	0.06 in (1.5 mm)
	Rear	0.08 in (2.0 mm)
Spark plug	(standard)	DCPR6E (NGK) or XU20EPR-U (DENSO)
	(high speed riding)	DCPR7E (NGK) or XU22EPR-U (DENSO)
Spark plug gap		0.03 - 0.04 in (0.8 - 0.9 mm)
Idle speed	(non-adjustable)	930 ± 100 rpm

Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	
	After draining	3.7 US qt (3.5 L)
Engine oil capacity	After draining & engine oil filter change	3.9 US qt (3.7 L)
	After disassembly	4.5 US qt (4.3 L)
Recommended final drive oil	Hypoid gear oil SAE 80	
Final drive oil capacity	After draining	4.4 US oz (130 cm ³)
	After disassembly	5.7 US oz (170 cm ³)
Recommended brake fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	2.68 US qt (2.54 L)	
Recommended coolant	Pro Honda HP Coolant	