

## ■ Service Data

Tire size	Front	120/90-17M/C (64S)
	Rear	160/80-15M/C (74S)
Tire type	bias-ply, tube	
Recommended Tires	Front	DUNLOP D404 FG
		BRIDGESTONE G701
	Rear	CHENG SHIN M6002
		DUNLOP D404
Tire air pressure	Front	29 psi (200 kPa, 2.00 kgf/cm <sup>2</sup> )
	Rear	29 psi (200 kPa, 2.00 kgf/cm <sup>2</sup> )* <sup>1</sup> 36 psi (250 kPa, 2.50 kgf/cm <sup>2</sup> )* <sup>2</sup>
Minimum tread depth	Front	0.06 in (1.5 mm)
	Rear	0.08 in (2.0 mm)
Spark plugs	(standard)	DPR7EA-9 (NGK) or X22EPR-U9 (DENSO)
	(high speed riding)	DPR8EA-9 (NGK) or X24EPR-U9 (DENSO)
	(non-adjustable)	0.031 to 0.035 in (0.80 to 0.90 mm)
Spark plug gap		
Idle speed	1,200 ± 100 rpm	

\*1 With less than 200 lb (90 kg) of added weight.

\*2 With more than 200 lb (90 kg) of added weight.

Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	
	After draining	2.6 US qt (2.5 liters)
Engine oil capacity	After draining & filter change	2.7 US qt (2.6 liters)
	After disassembly	3.4 US qt (3.2 liters)
	Recommended final drive oil	Hypoid gear oil SAE 80
Final drive oil capacity	After draining	5.4 US oz (160 cm <sup>3</sup> )
	After disassembly	5.7 US oz (170 cm <sup>3</sup> )
Recommended brake (clutch) fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	2.07 US qt (1.96 liters)	
Recommended coolant	Pro Honda HP Coolant	