

Specifications

■ Bulbs

Headlight	12V-60/55W
Brake/Taillight	12V-21/5W
Front turn signal lights	12V-21/5W x 2
Rear turn signal lights	12V-21W x 2
License plate light	12V-5W

■ Fuses

Main fuse	30A
FI fuse	VT750C 15A
	VT750C ABS 20A
Other fuses	VT750C 20A, 10A
	VT750C ABS 30A, 20A, 10A

■ Torque Specifications

Engine oil drain bolt	22 lbf·ft (30 N·m, 3.1 kgf·m)
Oil filter	19 lbf·ft (26 N·m, 2.7 kgf·m)
Final drive oil fill hole cap	9 lbf·ft (12 N·m, 1.2 kgf·m)
Final drive oil drain bolt	9 lbf·ft (12 N·m, 1.2 kgf·m)
Front wheel axle bolt	44 lbf·ft (59 N·m, 6.0 kgf·m)
Front wheel axle pinch bolts	16 lbf·ft (22 N·m, 2.2 kgf·m)
Rear brake stopper arm nut	16 lbf·ft (22 N·m, 2.2 kgf·m)
Rear wheel axle nut	65 lbf·ft (88 N·m, 9.0 kgf·m)
Rear wheel axle holding bolt	20 lbf·ft (27 N·m, 2.8 kgf·m)
Rear brake bracket bolt	51 lbf·ft (69 N·m, 7.0 kgf·m)
Exhaust pipe joint nuts	18 lbf·ft (25 N·m, 2.5 kgf·m)
Muffler bracket nut	20 lbf·ft (27 N·m, 2.8 kgf·m)
Footpeg bolt A, B and nut	29 lbf·ft (39 N·m, 4.0 kgf·m)