

## ■ Service Data

|                                                                            |                                                                                                                                                                                                                                           |                                             |
|----------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|
| Tire size                                                                  | Front                                                                                                                                                                                                                                     | 100/80-14M/C 48P                            |
|                                                                            | Rear                                                                                                                                                                                                                                      | 120/70-14M/C 61P                            |
| Tire type                                                                  |                                                                                                                                                                                                                                           | Bias-ply, tubeless                          |
| Recommended Tires                                                          | Front                                                                                                                                                                                                                                     | IRC SCT-006                                 |
|                                                                            | Rear                                                                                                                                                                                                                                      | IRC SCT-007                                 |
| Tire air pressure<br>(With less than<br>200 lb (90 kg) of<br>added weight) | Front                                                                                                                                                                                                                                     | 29 psi (200 kPa, 2.00 kgf/cm <sup>2</sup> ) |
|                                                                            | Rear                                                                                                                                                                                                                                      | 33 psi (225 kPa, 2.25 kgf/cm <sup>2</sup> ) |
| Tire air pressure<br>(With more than<br>200 lb (90 kg) of<br>added weight) | Front                                                                                                                                                                                                                                     | 29 psi (200 kPa, 2.00 kgf/cm <sup>2</sup> ) |
|                                                                            | Rear                                                                                                                                                                                                                                      | 36 psi (250 kPa, 2.50 kgf/cm <sup>2</sup> ) |
| Minimum tread depth                                                        | Front                                                                                                                                                                                                                                     | 0.06 in (1.5 mm)                            |
|                                                                            | Rear                                                                                                                                                                                                                                      | 0.08 in (2.0 mm)                            |
| Spark plug                                                                 | (standard)                                                                                                                                                                                                                                | MR8K-9 (NGK)                                |
| Spark plug gap                                                             |                                                                                                                                                                                                                                           | 0.03 - 0.04 in (0.8 - 0.9 mm)               |
| Idle speed                                                                 | (non-adjustable)                                                                                                                                                                                                                          | 1,700 ± 100 rpm                             |
| Recommended engine oil                                                     | API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE10W-30, JASO T 903 standard MB, Pro Honda HP4M 4-stroke oil or an equivalent motorcycle oil |                                             |

|                           |                                           |                     |
|---------------------------|-------------------------------------------|---------------------|
| Engine oil capacity       | After draining                            | 0.8 US qt (0.8 L)   |
|                           | After draining & cleaning strainer screen | 1.0 US qt (0.9 L)   |
|                           | After disassembly                         | 1.0 US qt (0.9 L)   |
| Transmission oil capacity | After draining                            | 0.13 US qt (0.12 L) |
|                           | After disassembly                         | 0.15 US qt (0.14 L) |
| Recommended brake fluid   | Honda DOT 3 or DOT 4 Brake Fluid          |                     |
| Cooling system capacity   |                                           | 0.51 US qt (0.48 L) |
| Recommended coolant       | Pro Honda HP Coolant                      |                     |