## **Specifications**

## **■** Main Components

Overall length	67.3 in (1,710 mm)		
Overall width	29.7 in (755 mm)		
Overall height	40.6 in (1,030 mm)		
Wheelbase	45.5 in (1,155 mm)		
Minimum ground clearance	6.3 in (160 mm)		
Caster angle	25° 00′		
Trail	3.2 in (82 mm)		
Curb weight	Monkey125	231 lb (105 kg)	
	Monkey125A	236 lb (107 kg)	
Maximum weight capacity *1	229 lb (104 kg)		
Passenger	Rider only		
capacity			
Minimum turning radius	6.2 ft (1.9 m)		

<sup>\*1:</sup> Including rider, all luggage, and accessories.

Displacement *1	7.6 cu-in (125 cm <sup>3</sup> )		
Bore x stroke	2.06 x 2.28 in (52.4 x 57.9 mm)		
Compression ratio	9.3 : 1		
Fuel	Unleaded gasoline Recommended: 86 PON or higher		
Tank capacity	1.48 US gal (5.6 L)		
Battery	YTZ5S 12 V-3.5 Ah (10 HR)		
Gear ratio	1st	2.500	
	2nd	1.550	
	3rd	1.150	
	4th	0.923	
Reduction ratio (primary / final)	3.350 / 2.266		

<sup>\*1:</sup> Displacement less than 9.2 cu-in (150 cm ³) may have highway operating restrictions depending on state laws.