

Frame	Item	Q'ty	Thread dia. (mm)	Torque N·m (kg-m, ft-lb)	Remarks
Brake:					
	Brake pedal pinch bolt	1	8	27 (2.7, 20)	Note 12
	Front caliper bracket bolt	4	8	31 (3.1, 22)	Note 12
	Rear caliper bracket bolt	1	8	23 (2.3, 17)	
	Brake hose bolt	7	10	35 (3.5, 25)	
	Rear brake hose mounting bolt	2	6	9 (0.9, 6.5)	Note 2
	Brake lever pivot nut	1	6	6 (0.6, 4.3)	
	Brake caliper bleed valve	3	8	5.5 (0.55, 4.0)	
	Pad pin plug	3	10	2.5 (0.25, 1.8)	
	Pad pin	3	10	18 (1.8, 13)	
	Front caliper pin bolt	2	8	23 (2.3, 17)	Note 2
	Front caliper bracket pin bolt	2	8	13 (1.3, 9)	Note 2
	Rear caliper pin bolt	1	12	28 (2.8, 20)	
	Front master cylinder holder bolt	2	6	12 (1.2, 9)	
	Rear master cylinder mounting bolt	2	6	9 (0.9, 6.5)	
	Rear reservoir tank mounting bolt	2	6	12 (1.2, 9)	
	Reservoir hose joint mounting screw	1	4	1.5 (0.15, 1.1)	Note 2
	Master cylinder push rod lock nut	1	8	18 (1.8, 13)	
	Front brake disc bolt	12	8	42 (4.2, 30)	Note 12
	Rear brake disc bolt	4	8	42 (4.2, 30)	Note 12
Frame/Exhaust Systems:					
	Ignition switch mounting bolt	2	8	25 (2.5, 18)	
	Exhaust pipe joint nut	8	7	20 (2.0, 14)	
	Exhaust pipe band bolt	2	8	27 (2.7, 20)	
	Muffler center mounting bolt	1	8	27 (2.7, 20)	
	Muffler center stay mounting bolt	2	10	40 (4.0, 29)	
	Muffler mounting bolt	2	10	40 (4.0, 29)	
	Exhaust pipe cover mounting bolt	6	6	9 (0.9, 6.5)	
	Side stand pivot bolt	1	10	10 (1.0, 7.2)	
	Side stand pivot nut	1	10	40 (4.0, 29)	Note 11
	Center stand pivot bolt	2	10	40 (4.0, 29)	
	Side stand switch mounting bolt	1	6	10 (1.0, 7.2)	Note 12
	Front fender mounting bolt	4	2	12 (1.2, 9)	
	Rear fender mounting bolt	2	2	12 (1.2, 9)	
	Turn signal mounting nut	4	12	55 (5.5, 40)	
	Grab rail mounting bolt	4	8	27 (2.7, 20)	
	Grab rail stay mounting bolt	4	8	27 (2.7, 20)	
	Seat lock mounting bolt	1	6	12 (1.2, 9)	
	Headlight mounting bolt	2	8	27 (2.7, 20)	
	Horn mounting bolt	1	8	27 (2.7, 20)	
	Footpeg rubber mounting bolt	4	5	5 (0.5, 3.6)	
	Footpeg mounting bolt	4	8	27 (2.7, 20)	
	Engine front mounting bolt	1	10	50 (5.0, 36)	
	Engine front bracket bolt	4	8	40 (4.0, 29)	
	Right engine lower bracket bolt	2	8	40 (4.0, 29)	
	Engine lower mounting bolt (Left)	1	10	60 (6.0, 43)	
	Engine lower mounting bolt (Right)	1	10	50 (5.0, 36)	
	Engine rear mounting bolt	1	10	50 (5.0, 36)	
	Engine rear bracket bolt	2	8	40 (4.0, 29)	