

# Maintenance Schedule

'90-'93:

Perform the PRE-RIDE INSPECTION in the Owner's Manual at each scheduled maintenance period.

I: Inspect and Clean, Adjust, Lubricate, or Replace if necessary.

R: Replace, L: Lubricate

The following items require some mechanical knowledge. Certain items (particularly those marked \* and \*\*) may require more technical information and tools. Consult your authorized Honda dealer.

Item	Frequency	Whichever Comes First Note	Odometer Reading (Note 1)								Refer to page
			× 1000 mi	0.6	4	8	12	16	20	24	
			× 1000 km	1	6	12	18	24	30	36	
EMISSION RELATED ITEMS	* Fuel Line				I			I		I	Note 5
	* Throttle Operation				I			I		I	Note 5
	* Carburetor Choke				I			I		I	Note 5
	Air Cleaner	Note 2					R			R	3-6
	Spark Plug			I	R	I	R	I	R		3-7/Note 5
	* Valve Clearance		I					I			3-7
	Engine Oil		R			R		R		R	Note 5
	Engine Oil Filter		R			R		R		R	Note 5
	* Carburetor Synchronization		I		I			I		I	3-11/Note 5
	* Carburetor Idle Speed		I	I	I	I	I	I	I	I	Note 5
	Radiator Coolant	Note 3				I		I		R	Note 5
	* Cooling System					I		I		I	Note 5
	* Secondary Air Supply System					I		I		I	Note 5
	* Evaporative Emission Control System	Note 4						I		I	Note 5
NON-EMISSION RELATED ITEMS	Drive Chain		I, L every 600 mi (1,000km)								3-12
	Brake Fluid	Note 3			I	I	R	I	I	R	Note 5
	Brake Pad Wear				I	I	I	I	I	I	Note 5
	Brake System		I			I		I		I	Note 5
	* Brake Light Switch					I		I		I	Note 5
	* Headlight Aim					I		I		I	3-15
	Clutch System					I		I		I	Note 5
	Clutch Fluid	Note 3			I	I	R	I	I	R	Note 5
	Side Stand					I		I		I	3-15
	* Suspension					I		I		I	Note 5
	* Nuts, Bolts, Fasteners		I			I		I		I	Note 5
	** Wheels/Tires					I		I		I	Note 5
** Steering Head Bearings		I			I		I		I	Note 5	

- \* Should be serviced by an authorized Honda dealer, unless the owner has proper tools and service data and is mechanically qualified.
- \*\* In the interest of safety, we recommend these items be serviced only by an authorized Honda dealer.

- Notes:
1. At higher odometer readings, repeat at the frequency interval established here.
  2. Service more frequently when riding in unusually wet or dusty areas.
  3. Replace every 2 years, or at indicated odometer interval, whichever comes first.  
Replacement requires mechanical skill.
  4. California type only.
  5. Refer to the Common Service Manual.